

### Amendments to the Claims

This Listing of Claims will replace all prior versions, and listings of claims in the application:

1. (Currently Amended) A method for initiating a Wireless Access Protocol (WAP) push session to push information from a push proxy gateway to a mobile station in a wireless communication network, the method comprising:

transmitting an initiation request to the mobile station by establishing using a connection-oriented signalling channel between the network and the mobile station and using said channel to transmit said request such that said mobile station activates a bearer for, said mobile station establishing a push session in response to the initiation request towards the push proxy gateway to permit the push proxy gateway to push information to the mobile station using the activated bearer.

2. (Currently Amended) The method of claim 1 wherein the activated bearer is a GPRS Packet Data Protocol Context. ~~connection-oriented signalling channel transmits the initiation request without using a store and forward mechanism.~~

3. (Currently Amended) The method of claim 1 wherein the connection-oriented signalling channel transmits the initiation request using a session oriented mechanism. ~~initiation request comprises an identification of the push proxy gateway for establishing the push session.~~

4. (Currently Amended) The method of claim 1 wherein the initiation request comprises an identification of ~~[[a]]~~ the bearer for activating to support the establishing of the push session.

5. (Currently Amended) The method of claim 1 further comprising providing an error message to the push proxy gateway ~~immediately~~ when said transmitting comprises failing to establish a session between the network and the mobile station using the connection-oriented signalling channel.

6. (Original) The method of claim 1 wherein the connection-oriented signalling channel comprises a channel for transmitting Unstructured Supplementary Service Data (USSD).
7. (Original) The method of claim 6 wherein the initiation request conforms to a WAP protocol for Service Initiation Requests (SIRs).
8. (Original) The method of claim 6 wherein the initiation request conforms to a USSD protocol for Unstructured Supplementary Service Requests (USSRs).
9. (Original) The method of claim 8 comprising: establishing a connection with the mobile station using the channel for transmitting USSD; and sending a USSR message requesting the mobile station to activate a Packet Data Protocol (PDP) context and establish a push session with the push proxy gateway.
10. (Original) The method of claim 1 comprising receiving the initiation request from the push proxy gateway.
11. (Currently Amended) A method for initiating a Wireless Access Protocol (WAP) push session to receive push information from a push proxy gateway at a mobile station in a wireless communication network, the method comprising:  
establishing a connection-oriented signalling channel between the network and the mobile station and receiving an initiation request at the mobile station using said channel; ~~a connection-oriented signalling channel between the network and the mobile station~~; and  
activating a bearer for establishing a push session in response to the initiation request towards the push proxy gateway to permit the push proxy gateway to push information to the mobile station using the activated bearer.
12. (Currently Amended) The method of claim 11 wherein the activated bearer is a

GPRS Data Protocol Context ~~wherein the connection-oriented signalling channel transmits the initiation request without using a store-and-forward mechanism.~~

13. (Original) The method of claim 11 wherein the initiation request comprises an identification of the push proxy gateway for establishing the push session.

14. (Original) The method of claim 11 wherein the initiation request comprises an identification of a bearer for activating to support the establishing of the push session.

15. (Original) The method of claim 11 wherein the connection-oriented signalling channel comprises a channel for transmitting Unstructured Supplementary Service Data (USSD).

16. (Original) The method of claim 15 wherein the initiation request conforms to a WAP protocol for Service Initiation Requests (SIRs).

17. (Original) The method of claim 15 wherein the initiation request conforms to a USSD protocol for Unstructured Supplementary Service Requests (USSRs).

18. (Currently Amended) The method of claim 11 wherein the connection-oriented signalling channel transmits the initiation request using a session oriented mechanism. ~~17 comprising: establishing a connection with the network using the channel for transmitting USSD; and receiving a USSR message requesting the mobile station to activate a Packet Data Protocol (PDP) context and establish a push session with the push proxy gateway.~~

19. (Original) The method as defined in claim 11 comprising providing the initiation request to a Session Initiation Application of the mobile station, the application adapted in accordance with a WAP protocol for initiating a push session.

20. (Currently Amended) ~~In a push proxy gateway adapted to push information to a mobile station in a wireless communication network, a~~ A method for initiating a Wireless

Access Protocol (WAP) push session ~~between the~~ in a push proxy gateway adapted to push information to a ~~and the mobile station in a wireless communication network~~ comprising:

transmitting an initiation request to a network node of the wireless communication network for delivery to the mobile station by establishing using a connection-oriented signalling channel between the network and the mobile station and using said channel to transmit said request, and communicating with said mobile station in order to activate a bearer for said mobile station establishing a push session in response to the initiation request towards the push proxy gateway to permit the push proxy gateway to push information to the mobile station using said activated bearer.

21. (Currently Amended) The method of claim 20 wherein the activated bearer is a GPRS Packet Data Protocol Context ~~connection-oriented signalling channel transmits the initiation request without using a store and forward mechanism.~~

22. (Original) The method of claim 20 wherein the initiation request comprises an identification of the push proxy gateway for establishing the push session.

23. (Currently Amended) The method of claim 20 wherein the initiation request comprises an identification of ~~[[a]]~~ the bearer for activating to support the establishing of the push session.

24. (Currently Amended) The method of claim 20 further comprising receiving an error message at the push proxy gateway ~~immediately~~ when said network fails to establish a session between the network and the mobile station using the connection-oriented signalling channel.

25. (Original) The method of claim 20 wherein the connection-oriented signalling channel comprises a channel for transmitting Unstructured Supplementary Service Data (USSD).

26. (Original) The method of claim 25 wherein the initiation request conforms to a WAP protocol for Service Initiation Requests (SIRs).
27. (Original) The method of claim 25 wherein the initiation request conforms to a USSD protocol for Unstructured Supplementary Service Requests (USSRs).
28. (Currently Amended) The method of claim 20 wherein the connection-oriented signalling channel transmits the initiation request using a connection-oriented mechanism. ~~27 comprising: sending a USSR message requesting the mobile station to activate a Packet Data Protocol (PDP) context and establish a push session with the push proxy gateway.~~
29. (Currently Amended) A network node of a wireless communication network for initiating a Wireless Access Protocol (WAP) push session to push information from a push proxy gateway to a mobile station via the wireless communication network, the network node comprising:
- a communications system for transmitting and receiving via the wireless network;
  - a processor coupled to the communication system for processing received messages and messages for sending; and
  - a memory coupled to the processor for storing instructions to configure the processor to:
- transmit an initiation request to the mobile station by establishing a connection-oriented signalling channel between the network and the mobile station and using a connection-oriented signalling said channel to transmit said request such that said mobile station activates a bearer for ~~between the network and the mobile station, said mobile station establishing a push session in response to the initiation request towards the push proxy gateway to permit the push proxy gateway to push information to the mobile station using said activated bearer.~~
30. (Currently Amended) A mobile station for initiating a Wireless Access Protocol

(WAP) push session to receive push information from a push proxy gateway via a wireless communication network, the mobile station comprising:

- a communications system for transmitting and receiving via the wireless network;
- a processor coupled to the communication system for processing received messages and messages for sending; and
- a memory coupled to the processor for storing instructions to configure the processor to:

- ~~receive an initiation request at the mobile station using~~ establish a connection-oriented signalling channel between the network and the mobile station and receive an initiation request at the mobile station using said channel; and

- activate a bearer to establish a push session in response to the initiation request towards the push proxy gateway to permit the push proxy gateway to push information to the mobile station.

31. (Currently Amended) A push proxy gateway for initiating a Wireless Access Protocol (WAP) push session to push information from the push proxy gateway to a mobile station via a wireless communication network, the push proxy gateway comprising:

- a communications system for transmitting and receiving via the wireless network;
- a processor coupled to the communication system for processing received messages and messages for sending; and
- a memory coupled to the processor for storing instructions to configure the processor to:

- transmit an initiation request to a network node of the wireless communication network for delivery to the mobile station ~~using~~ by establishing a connection-oriented signalling channel between the network and the mobile station and using said channel to transmit said request such that said mobile station activates a bearer for, ~~said mobile station~~ establishing a push session in response to the initiation request towards the push proxy gateway to permit the push proxy gateway to push information to the mobile station using said activated bearer.